



MATERIAL 706B

SAFETY DATA SHEET



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Issuing Date 26-Sep-2021 Revision Date 26-Sep-2021 Revision Number 2.04

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code(s) SDS-06199 EN E

Product Name Support, SUP706 B™

PN (Part Number) OBJ-03046, OBJ-04042, OBJ-18016

Denmark

PR No N/A

Chemical name Acrylic formulation

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Printing inks

Uses advised against

This product is a cartridge containing ink. Under normal conditions of use, the substance is

released from a cartridge only inside an appropriate printing system, and therefore,

exposure is limited

1.3. Details of the supplier of the safety data sheet

Importer

Stratasys EMEA Regional Office

Airport Boulevard B 120

77836 Rheinmünster, Germany Phone: +49-7229-7772-0

For further information, please contact

E-mail address info@Stratasys.com

1.4. Emergency telephone number

Emergency Telephone +44 1235 239670 - Europe - Multi lingual response

Austria Poison Information Centre (AT): +43-(0)1-406 43 43

 Belgium
 Poison Centre (BE): +32 70 245 245

 Bulgaria
 Poison Center (BG): +359 (0)2 9154 233

 Croatia
 Poison Control (CR): +385 1 2348 342

Czech Republic Poison Control (CS): +420 224 919 293, +420 224 915 402

 Denmark
 Poison Control Hotline (DK): +45 82 12 12 12

 Estonia
 Poison Control (ET): 112, 16662, +372 7943 794

 Finland
 Poison Information Centre (FI): +358 9 471 977

France ORFILA (FR): + 01 45 42 59 59

Greece Poison Information Center (EL): +30 210 779 3777 Emergency Poison Centre telephone

number, Aglaia Kyriakou Children's Hospital

Hungary Poison Information Service (HU): +36 (06) 80 201-199

EN / EGHS Page 1/13

Ireland +353 (0)1 809 2166 – public poisons information line **Italy** Poison Centre, Milan (IT): +39 02 6610 1029

Latvia State Fire and Rescue Service, phone number: 112. State Toxicology Center, Poisoning

and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1079, phone number +371

67042473

Lithuania Poison Information Office (LT): 112, +370 (8)5 236 20 52, +370 (8)6 875 33 78

Netherlands National Poisons Information Center (NVIC): 030-274 8888 (Only for the purpose of

informing medical personnel in cases of acute intoxications)

NorwayPoisons Information (NO): + 47 22 591300PortugalPoison Information Centre (PT): +351 808 250 250SlovakiaPoison Information Service (SK): +421 911 166066SpainPoison Information Service (ES): +34 91 562 04 20

Sweden 112 – ask for Poisons Information **Switzerland** Tox Info Suisse: 145, +41 44 251 51 51

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label elements

Contains N-hydroxyethylacrylamide, Acrylic acid, 2-hydroxyethyl ester



Signal word Danger

Hazard statements

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P260 - Do not breathe vapour

P280 - Wear protective gloves and eye/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Harmful to aquatic life.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

EN / EGHS Page 2/13

3.1 Substances

3.2 Mixtures

Chemical name	EC No	CAS No	Index no.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Propane-1,2-diol	200-338-0	57-55-6	-	10 - 30	Not classified	01-2119456809-23-000 6
Polyethylene Glycol 400	-	25322-68-3	-	10 - 30	Not classified	No data available
Proprietary	Not Listed	-	-	3-10	Eye Dam. 1 (H318) STOT RE 2 (H373)	01-2119422483-45-XXX X
Acrylic acid, 2-hydroxyethyl ester	212-454-9	818-61-1	607-072-00-8	1-3	Acute Tox. 4 (H302) Acute Tox. 2 (H310) Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) STOT SE 3 (H335) Aquatic Acute 1 (H400) Aquatic Chronic 3 (H412)	No data available
4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	-	55818-57-0	-	0.3-1	Skin Sens. 1 (H317)	01-2119490020-53-XXX X
Ethoxylated Trimethylolpropane Triacrylate	=	28961-43-5	-	0.3-1	Skin Sens. 1B (H317) Eye Irrit. 2 (H319)	No data available
4-Methoxyphenol/ Mequinol	205-769-8	150-76-5	-	0.1 - 0.3	Acute Tox. 4 (H302) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Repr. 2 (H361d) Aquatic Chronic 3 (H412)	No data available
2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol	204-881-4	128-37-0	-	0.1 - 0.3	Acute Tox. 4 H302 Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	No data available
Heptane	205-563-8	142-82-5	-	<0.1	Skin Irrit. 2 (H315) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Flam. Liq. 2 (H225)	No data available

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Get immediate medical advice/attention. Rinse immediately with plenty of water, also under

the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an

allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

EN / EGHS Page 3/13

Symptoms Burning sensation. Itching. Rashes. Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsMay cause sensitisation in susceptible persons. Treat symptomatically.

Section 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire

Class B fires: Use carbon dioxide (CO2), regular dry chemical (sodium bicarbonate), regular foam (Aqueous Film Forming Foam-AFFF), or water spray to cool containers

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

Product is or contains a sensitiser. May cause sensitisation by skin contact.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Move containers from fire area if you can do it without risk. Cool containers with flooding quantities of water until well after fire is out. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Keep out of drains, sewers, ditches and waterways. Inhalation is a health risk. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from

and upwind of spill/leak.

Occupational Spill Release Intact cartridges do not pose a leak or spill hazard. Damaged cartridges may leak uncured

ink. Stop leak if you can do it without risk Use water spray to reduce vapours or divert vapour cloud drift Absorb spill with inert material (e.g. dry sand or earth), then place in a

chemical waste container Keep out of drains, sewers, ditches and waterways

Other Information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containmentUse a non-combustible material like vermiculite, sand or earth to soak up the product and

place into a container for later disposal. Following product recovery, flush area with water.

Methods for cleaning upTake up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

EN / EGHS Page 4/13

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling Avoid breathing vapours or mists. Wash thoroughly after handling. Obtain special

instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Do

not eat, drink or smoke when using this product.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do

not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other

chemicals. Store in a cool, well ventilated area. Store in accordance with local regulations. Keep container tightly closed. Store between 15 °C and 27 °C. Shipment temperature (up to 5 weeks) is -20 °C to 50 °C. Store in a combustible storage area away from heat and open

flame.

Hints on joint storage

Storage class LGK10 - Combustible liquids unless storage class 3

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Material Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure disclaimer Personal protection measures are only needed if cartridge is damaged punctured causing

spillage of material.

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom	France	Spain	Germany
Propane-1,2-diol	-	TWA: 150 ppm	-	-	-
57-55-6		TWA: 474 mg/m ³			
		TWA: 10 mg/m ³			
		STEL: 450 ppm			
		STEL: 1422 mg/m ³			
		STEL: 30 mg/m ³			
Polyethylene Glycol 400	-	-	-	-	TWA: 200 mg/m ³
25322-68-3					
4-Methoxyphenol/	-	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³	-
Mequinol					
150-76-5					
2,6-Bis(1,1-Dimethylethyl	-	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
)-4-Methyl-Phenol		STEL: 30 mg/m ³			
128-37-0					

EN / EGHS Page 5/13

Heptane 142-82-5	TWA 500 ppm TWA 2085 mg/m³	TWA: 500 ppm TWA: 2085 mg/m³ STEL: 1500 ppm STEL: 6255 mg/m³	TWA: 400 ppm TWA: 1668 mg/m³ TWA: 1000 mg/m³ STEL: 500 ppm STEL: 2085 mg/m³ STEL: 1500 mg/m³	TWA: 500 ppm TWA: 2085 mg/m³	TWA: 500 ppm TWA: 2100 mg/m³
Chemical name	Italy	Portugal	Netherlands	Finland	Denmark
Polyethylene Glycol 400 25322-68-3	-	-	-	-	TWA: 1000 mg/m ³
Acrylic acid, 2-hydroxyethyl ester 818-61-1	-	-	-	•	TWA: 1 ppm TWA: 5 mg/m³ H*
4-Methoxyphenol/ Mequinol 150-76-5	-	TWA: 5 mg/m ³	-	-	TWA: 5 mg/m ³
2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol 128-37-0	-	TWA: 2 mg/m ³	-	TWA: 10 mg/m ³ STEL: 20 mg/m ³	TWA: 10 mg/m ³
Heptane 142-82-5	TWA: 500 ppm TWA: 2085 mg/m ³	TWA: 500 ppm TWA: 2085 mg/m³ STEL: 500 ppm	TWA: 1200 mg/m ³ STEL: 1600 mg/m ³	TWA: 300 ppm TWA: 1200 mg/m³ STEL: 500 ppm STEL: 2100 mg/m³	TWA: 200 ppm TWA: 820 mg/m ³
Chemical name	Austria	Switzerland	Poland	Norway	Ireland
Propane-1,2-diol 57-55-6	-	-	TWA: 100 mg/m ³	TWA: 25 ppm TWA: 79 mg/m³ STEL: 37.5 ppm STEL: 118.5 mg/m³	TWA: 10 mg/m ³ TWA: 150 ppm TWA: 470 mg/m ³ STEL: 1410 mg/m ³ STEL: 30 mg/m ³ STEL: 450 ppm
Polyethylene Glycol 400 25322-68-3	TWA: 1000 mg/m ³ STEL 4000 mg/m ³	TWA: 500 mg/m ³	-	-	-
4-Methoxyphenol/ Mequinol 150-76-5	TWA: 5 mg/m ³ STEL 10 mg/m ³	-	TWA: 5 mg/m ³	TWA: 5 mg/m³ STEL: 10 mg/m³	TWA: 5 mg/m³ STEL: 15 mg/m³
2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol 128-37-0	TWA: 10 mg/m ³	TWA: 10 mg/m³ STEL: 40 mg/m³	-	1	TWA: 2 mg/m ³ STEL: 6 mg/m ³
Heptane 142-82-5	TWA: 500 ppm TWA: 2000 mg/m ³ STEL 2000 ppm STEL 8000 mg/m ³	TWA: 400 ppm TWA: 1600 mg/m ³ STEL: 400 ppm STEL: 1600 mg/m ³	STEL: 2000 mg/m ³ TWA: 1200 mg/m ³	TWA: 200 ppm TWA: 800 mg/m³ TWA: 40 ppm TWA: 275 mg/m³ STEL: 250 ppm STEL: 1000 mg/m³ STEL: 60 ppm STEL: 343.75 mg/m³	TWA: 500 ppm TWA: 2085 mg/m³ STEL: 1500 ppm STEL: 6255 mg/m³

Chemical name	Sweden	Slovakia			
Polyethylene Glycol 400	-	TWA: 1000 mg/m ³		=	=
25322-68-3					
Acrylic acid,	NGV: 1 ppm			-	-
2-hydroxyethyl ester	NGV: 5 mg/m ³				
818-61-1	Sensitizer				
	*				
	Vägledande KGV: 2				
	ppm				
	Vägledande KGV:				
	10 mg/m ³				
Heptane	NGV: 200 ppm	TWA: 500 ppm	-	-	-
142-82-5	NGV: 800 mg/m ³	TWA: 2085 mg/m ³			

EN / EGHS Page 6/13

Chemical name	Sweden	Slovakia		
	NGV: 350 mg/m ³			
	Vägledande KGV:			
	300 ppm			
	Vägledande KGV:			
	1200 mg/m ³			

Derived No Effect Level (DNEL) No information available.

Predicted No Effect Concentration

No information available.

(PNEC)

8.2. Exposure controls

Personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand Protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do **General hygiene considerations**

not eat, drink or smoke when using this product.

No information available. **Environmental exposure controls**

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Liquid **Appearance** Ink cartridge Odour Characteristic Colour vellow

Odour threshold No information available

Property Values Remarks • Method

N/A pН

Melting point / freezing point No data available None known Boiling point / boiling range No data available None known

Flash point 111 - 113 °C IP 523 Procedure B, CC (closed cup)

Evaporation rate No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability limit: No data available Lower flammability limit No data available

Vapour pressure No data available None known No data available Vapour density None known 1.10 g/cm3 Relative density

Soluble in water Water solubility

Solubility(ies) No data available None known **Partition coefficient** No data available None known **Autoignition temperature** No data available None known

EN / EGHS Page 7/13

Decomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Explosive properties No information available Oxidising properties No information available

9.2. Other information

Softening point
Molecular weight
VOC Content (%)
Liquid Density
Bulk density
Particle Size
Particle Size
No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity Heating may cause a fire.

10.2. Chemical stability

Stability Decomposes on exposure to light. Unstable if heated.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to heat and light.

10.5. Incompatible materials

Incompatible materialsNot applicable under normal conditions of use and storage.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal Decomposition Products. Combustion: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract. (based on components).

Eye contact Severely irritating to eyes. Causes serious eye damage. May cause burns. May cause

irreversible damage to eyes. (based on components).

Skin contact May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause

allergic reactions with susceptible persons. (based on components). Causes skin irritation.

EN / EGHS Page 8/13

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. (based on

components).

Information on toxicological effects

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and

tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 32,814.40 mg/kg

 ATEmix (dermal)
 2,994.60 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propane-1,2-diol	= 20 g/kg	= 20800 mg/kg (Rabbit)	-
	= 20 g/kg (Rat)		
Polyethylene Glycol 400	= 22 g/kg	> 20 g/kg (Rabbit)	-
	= 22 g/kg (Rat)		
Proprietary	-	> 2000 mg/kg (Rat)	-
Acrylic acid, 2-hydroxyethyl	= 548 mg/kg	> 1000 mg/kg (Rat)	-
ester	= 548 mg/kg (Rat)		
4,4'-isopropylidenediphenol,	>2000 mg/kg (Rat)	>2000 mg/kg	-
oligomeric reaction products			
with 1-chloro-2,3-epoxypropane,			
esters with acrylic acid			
Ethoxylated Trimethylolpropane	-	> 13200 mg/kg (Rabbit)	-
Triacrylate			
4-Methoxyphenol/ Mequinol	= 1600 mg/kg	> 2000 mg/kg (Rabbit)	-
	= 1600 mg/kg (Rat)		
2,6-Bis(1,1-Dimethylethyl)-4-Me	> 2930 mg/kg	> 2000 mg/kg (Rat)	-
thyl-Phenol	> 2930 mg/kg (Rat)		
Heptane	-	= 3000 mg/kg (Rabbit)	> 73.5 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Risk of serious

damage to eyes.

Respiratory or skin sensitisation May cause sensitisation by skin contact. Classification based on data available for

ingredients.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity
STOT - single exposure

No information available.
No information available.

STOT - repeated exposure Classification based on data available for ingredients.

Aspiration hazard No information available.

EN / EGHS Page 9/13

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects

Unknown aquatic toxicityContains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Propane-1,2-diol	19000: 96 h Pseudokirchneriella subcapitata mg/L EC50	41 - 47: 96 h Oncorhynchus mykiss mL/L LC50 static 51400: 96 h Pimephales promelas mg/L LC50 static 51600: 96 h Oncorhynchus mykiss mg/L LC50 static 710: 96 h Pimephales promelas mg/L LC50	-	1000: 48 h Daphnia magna mg/L EC50 Static
Proprietary	-	98: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	-	-
Acrylic acid, 2-hydroxyethyl ester	-	4.8: 96 h Pimephales promelas mg/L LC50 flow-through	-	0.78: 48 h Daphnia magna mg/L EC50
Ethoxylated Trimethylolpropane Triacrylate	-	1.95: 96 h Danio rerio mg/L LC50 static	-	-
4-Methoxyphenol/ Mequinol	-	28.5: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 84.3: 96 h Pimephales promelas mg/L LC50 flow-through	-	-
2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol	6: 72 h Pseudokirchneriella subcapitata mg/L EC50 0.42: 72 h Desmodesmus subspicatus mg/L EC50	-	-	-
Heptane	-	375.0: 96 h Cichlid fish mg/L LC50	-	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Acrylic acid, 2-hydroxyethyl ester	0.21
4-Methoxyphenol/ Mequinol	1.3
2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol	4.17
Heptane	4.66

12.4. Mobility in soil

Mobility in soil No information available.

EN / EGHS Page 10/13

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

Other adverse effects No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

Waste codes / waste designations

according to EWC / AVV

08 03 12* Waste ink containing dangerous substances.

Section 14: TRANSPORT INFORMATION

IMDG

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not applicable 14.5 Marine pollutant

14.6 Special Provisions None

14.7 Transport in bulk according to No information available

Annex II of MARPOL 73/78 and the

IBC Code

RID

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable None

14.6 Special Provisions

ADR

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

None

14.6 Special Provisions

IATA

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated Not applicable 14.5 Environmental hazards

None 14.6 Special Provisions

EN / EGHS Page 11/13

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number	Title
Propane-1,2-diol	RG 84	-
57-55-6		
Acrylic acid, 2-hydroxyethyl ester 818-61-1	RG 65	-
4-Methoxyphenol/ Mequinol 150-76-5	RG 65	-
Heptane 142-82-5	RG 84	-

Germany

Water hazard class (WGK) slightly hazardous to water (WGK 1)

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorisations and/or restrictions on use:

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH	Substance subject to authorisation per
	Annex XVII	REACH Annex XIV
Acrylic acid, 2-hydroxyethyl ester - 818-61-1	75.	
4-Methoxyphenol/ Mequinol - 150-76-5	75.	
Proprietary -	75.	
Heptane - 142-82-5	75.	

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

15.2. Chemical safety assessment

Chemical Safety Report No information available

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

EN / EGHS Page 12/13

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapor	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration toxicity	Calculation method
Ozone	Calculation method

Revision Date 26-Sep-2021

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet derives from a third party source. Whilst we believe that the information is correct as at the date of its publication, we do not make any representations or warranties regarding the accuracy or completeness of the information nor the quality or specification of any materials, substances or mixtures referred to herein (collectively, "Materials"). The information is being provided solely as a guideline for the safe handling, use, consumption, processing, storage, transportation, disposal and release of the Materials. The information may not be sufficient for such purposes and the user should not place any reliance on the information provided. The information may not be applicable to Materials that are combined with any materials or in any process other than as expressly stated herein. We shall not be liable for any kind of liability including, without limitation, damages, losses or expenses, arising out of or as a result of any reliance on the information contained in this Safety Data Sheet.

© 2018-2021 Stratasys Ltd. License granted to make unlimited paper/electronic copies for internal use only. This Safety Data Sheet or sections thereof should not be published, reproduced, modified, or distributed to third parties without prior written consent from Stratasys Ltd.

End of Safety Data Sheet

EN / EGHS Page 13/13