



STRATASYS SAFTM H350™



BROCHURE SAF


Stratasys[®] H350™

Accurate, production-grade parts with best-in-class* consistency.

Meet high production demands with the Stratasys H350 powder bed fusion 3D printer.







Grow your part production business for a variety of industries and applications with a workflow you can fully control. Built for high-volume, short-run production, the Stratasys H350 3D printer gives you control of your materials, workflow, production and costs while delivering consistency and accuracy print after print. The Stratasys H350 is the first release of the H Series" production platform, which has Selective Absorption Fusion" SAF" technology at its heart to deliver functional, production-grade parts with best-inclass* consistency.





Parts with No Hidden Costs.

With few consumables, easy upkeep and long-lasting industrial-grade print heads, the H350 printer has been designed to last. Maintenance and labor requirements are low, so you can maximize production uptime while minimizing running costs. Fewer restrictions in part orientation mean high nesting density, which maximizes the number of parts per build. If you choose to, you can reuse all of your unfused powder — keeping material costs down and significantly reducing cost per part.

A single fusing fluid also means a simple and predictable cost per part. Additionally, print heads are non-consumables and included as part of your service contract.

 $[\]mbox{\ensuremath{\star}}$ Compared to other powder bed fusion technologies using print heads.



Achieve Superior Part Quality and

Enhanced Aesthetics with SAF

HighDef Printing

Stratasys SAF technology, now equipped with HighDef Printing, brings 3D printed objects to life with enhanced aesthetics and unmatched detail. This innovative feature ensures high-volume parts with superior accuracy and high repeatability. With advanced thermal management and precise fluid deposition, SAF produces parts with consistent quality across fine feature details, flat areas, and large parts. The industry-leading narrowest gap clearance achieved by SAF HighDef ensures precise and tight fits in mechanisms and assemblies, making it ideal for a wide range of applications.



Maximize Process Flexibility and Boost Your Productivity


The H350 3D printer allows users to choose their build preparation software platforms to suit their business needs. With no mandatory cloud connection, no forced firmware updates and the ability to reuse previous print settings, you can have quality control of your production.

The H350's workflow also gives you complete control over your powder quality management and build data so that you can easily certify your production. Its stable process is supported by its industrial-grade components and consistent thermal process. Plus, print heads are not consumable items, so there's no need for frequent recertification — meaning the print process and performance remain steady.

The flexibility to tailor your own workflow empowers you to meet your customers' specifications for different application requirements. Save settings and reuse for repeat builds at any time. Reproduce precise, geometric measurements and mechanical properties to achieve part consistency. Monitor and adjust settings with few consumables, easy upkeep and long-lasting industrial-grade print heads, to produce the part qualities that meet the standards of each application.



H350 Workflow





SendSend print jobs to the printer.



Print
SAF technology provides
a uniform thermal
experience for improved
part consistency.

- A. Big Wave powder management system precisely and evenly deposits a new layer.
- **B.** The layer is immediately heated to maintain thermal homogeneity and ensure part quality.
- C. Industrial piezoelectric print heads jet high-energy HAF™ high absorption fluid on the powder.
- **D.** Infrared energy fuses the selected areas and underlying particles.



Build RemovalRemove a completed build to cool down.



Data Retrieval
Retrieve data from a build
job for quality control and
certify production.



Monitor

Monitor progress of all
printers in your fleet with
GrabCAD Print Server.

Additional Part-Finishing steps:



Breakout and Powder Retrieval Remove parts from a build and retrieve

unfused powder

8

DosingRetrieve unfused powder
and mix with virgin
material for printer refill.



7. Powder Refill
Put dosed powder
in the machine (e.g., 70:30
used-to-virgin ratio).



Depowdering/ Bead Blasting Use your choice of

Use your choice of equipment to remove any excess powder from the part surface to create a new raw part.



Adaptable Workflow









Powered by SAF technology

SAF technology is an industrial-grade additive manufacturing solution that delivers production-level throughput for end-use parts. This is achieved by selectively jetting HAF fluid with industrial piezoelectric print heads onto a layer of powder-form material in just one, full-width pass.

Thanks to its unique in-line, unidirectional architecture, SAF technology prints, fuses, recoats (with Big Wave powder system) and powder heats in the same direction. The time-controlled manner of these processes ensure a uniform thermal experience and part consistency across the whole bed.

SAF technology jets single or multiple drops of highly loaded fluids to produce fine detail or large fused areas without compromising throughput. It also has the ability to jet unique, high-specialty, functional fluids to process a broad range of powders and manufacture parts with selectively defined point-to-point properties.

Due to the savings of implementing industrial-grade technology, SAF-based products will deliver a competitive cost per part, production-level throughput, part quality and consistency, and a high production yield.

SAF technology jets single or multiple drops of highly loaded fluids to produce fine detail or large fused areas without compromising throughput.



^{*} The PowderEase T1 is an optional accessory. SAF workflow is opened for other material handling equipement.



Specifications

| Effective Build Size (xyz) 315 x 208 x 293 mm (12.40 x 8.18 x 11.53 in) Effective Build Volume 19.2 I (5.07 gallon) Layer Thickness 100 μ (0.004 in) Time to a Full Build 11.62 hrs. Power 400VAC, 3P+N+PE, 50/60 Hz, 16A | |
|---|--|
| Layer Thickness 100 μ (0.004 in) Time to a Full Build 11.62 hrs. Power Requirements 400VAC, 3P+N+PE, 50/60 Hz, 16A | |
| Time to a Full Build 11.62 hrs. Power Requirements 400VAC, 3P+N+PE, 50/60 Hz, 16A | |
| Power Requirements 400VAC, 3P+N+PE, 50/60 Hz, 16A | |
| Requirements 400VAC, 3P+N+PE, 50/60 Hz, 16A | |
| | |
| | |
| Consumption 3.25 kW, 5 kW (peak), 0.15 kW (Idle) | |
| Operating conditions | |
| Temperature 20-25° C (68-77 deg F) | |
| Humidity [40-55]% RH | |
| Extraction Rate 300m³/h (177 CFM) with adjustable damper | |
| Dimensions (W x D x H) | |
| Printer 1900 x 940 x 1730 mm (74.8 x 37.0 x 68.1 in) | |
| Printer crate 2156 x 1196 x 2100 mm (84.9 x 47.1 x 82.7 in) | |
| Weight | |
| Printer 825 kg (1819 lb) | |
| Crated Printer 950 kg (2094 lb) | |
| Connectivity | |
| Network Requirements RJ45 Ethernet connection 35MBit Network with DHCP server and Internet access recommended | |
| Software | |
| Supported Software Workflow GrabCAD Print, GrabCAD Print Pro GrabCAD Print Server Materialise Magics, Siemens NX and PTC Creo | |
| Certificates | |
| Safety EN ISO 12100:2010 | |
| Electromagnetic DIRECTIVE 2014/30/EU | |
| REACH, RoHS, WEEE, Modern Slavery Act, CoA, | |
| Environmental CoC (and from 2021, Conflict Minerals regulation), TSCA | |
| CoC (and from 2021, Conflict Minerals regulation), TSCA Materials | |
| Coc (and from 2021, Conflict Minerals regulation), 15CA | |
| Materials Materials | |
| Materials Powders Stratasys High Yield PA11, SAF*PA12, SAF*PP, SAF*ReLife* PA12 | |
| Materials Powders Stratasys High Yield PA11, SAF*PA12, SAF*PP, SAF*ReLife*PA12 Fluid Stratasys HAF™ high absorption fluid | |

^{*} H350 printer consumables refers to H350 parts that wear out relatively frequently and need replacement by the customer. For clarity, H350 printer consumables do not include H350 materials, HAF or powders, and do not include other materials required for the maintenance of the H350 such as cleaning fluids, gloves and swabs.



Looking to see if the Stratasys H350 is the right solution for your production needs? Visit **theD2Mco.com** to explore more about our additive manufacturing expertise. Whether you have questions about SAF™ technology, material compatibility, or how to scale your operations efficiently, our team is here to help.

Get in touch today for personalized guidance and discover how we can support your journey from design to manufacturing.



Get Expert Guidance on Your Additive Manufacturing Journey

From prototyping to production, our consultants help you choose the right printers, materials, and strategies to scale smarter.

TALK TO AN EXPERT

Visit https://theD2Mco.com/contact-us





