

TRACKSCAN-P Optical 3D Measurement System

Intelligent Tracking without Targets



Get Expert Guidance on Your 3D Scanning & Inspection Strategy

From reverse engineering to digital inspection, our consultants help you choose the right scanners, software, and workflows to scale smarter.

TALK TO AN EXPERT

Visit https://theD2Mco.com/contact-us





Supplied by theD2Mco.com

TRACKSCAN-P

Engineered with intelligent optical tracking measurement and high-resolution cameras, Track-Scan-P can precisely measure parts without having to stick reference targets. This optical 3D measurement system, consisting of a portable 3D scanner and an optical tracker i-Tracker, suits well for 3D scanning large-scale objects. It can be widely applied for quality control, product development, reverse engineering, and more in industries such as aerospace, automotive, rail transport, and mold.

By combining it with additional modules, it can enable extendable applications. It can be paired with an auxiliary light module to inspect circles, grooves, and machined holes of stamping parts. With a portable probe, it conducts precise contact measurements for edges, circles, and grooves. When being mounted onto a robot arm, it is an optimal choice for intelligent and



Optional auxiliary light module

Single point repeatability 0.030 mm



Intuitive operating indicator



Target-free 3D Scanning





21 blue laser crosses 2.6 million measurements/s

Anti-dust & fog targets Aerospace-grade carbon fiber



Wireless and portable

Dual-camera system for large-volume tracking





Extendable Measuring Volume



Optical Tracking for Instant 3D Scanning

TrackScan-P 3D system's optical tracking allows users to start scanning instantly without having to stick targets, significantly improving efficiency and decreasing costs.



Unrivaled-fast & Detail-maker

By freely switching between multiple working modes, the TrackScan fits different scanning situations with an accuracy of up to 0.025 mm and an ultra-fast measurement rate of up to 2,600,000 measurements/s. Its 7 parallel blue laser lines perform well for capturing details. A single blue laser line aims to collect 3D data of deep holes and hard-to-reach areas efficiently.



Strong Adaptability

Made from aerospace-grade materials, it is sturdy and reliable. It also boasts a strong anti-interference capability to operate smoothly regardless of vibrations or thermal variations. Due to its advanced algorithm, TrackScan is robust in capturing 3D data of reflective and dark surfaces.

Precise Edge Detection

TrackScan features a stand-out function of instant edge detection. Users can inspect circles, grooves, and machined holes of stamping parts in various finishes on the site without having to import original CAD models.The efficient edge detection is enabled thanks to its gray value measurement and optional auxiliary light module. Good measurements are ensured by delivering accurate and repeatable hole positions and diameters.



Extendable Applications

TrackScan-P optical 3D measurement system can be integrated with Scantech's products to cater to different measurement needs.





It can be paired with a portable prober (optional with different sizes) to probe inaccessible areas such as holes and hidden points. This contact measurement probe can ensure precise results with high single-point repeatability of 0.030 mm.

When integrated with Scantech's wireless communication link AirGo Pro, it can enable free and mobile 3D scanning.




It can be mounted on a robotic arm to form an automated 3D measurement system AutoScan-T for efficient, and batch measurement.



Technical specification

Туре		TrackScan-P550	TrackScan-P542
Scan mode	Ultra-fast scanning	21 blue laser crosses	17 blue laser crosses
	Hyperfine mode B	7 blue parallel laser lines	
	Deep hole scanning	1 extra blue laser line	
Accuracy ⁽¹⁾		Up to 0.025 mm (0.0009 in)	
Measurement rate up to		2,600,000 measurements/s	2,200,000 measurements/s
Scanning area up to		500 mm × 600 mm (19.7 in × 23.6 in)	
Laser class		Class II (eye-safe)	
Resolution up to		0.020 mm (0.0008 in)	
Volumetric ⁽²⁾ accuracy	10.4 m ³	0.060 mm (0.0024 in)	
	18.0 m ³	0.075 mm (0.0030 in)	
Volumetric accuracy (With MSCAN photogrammetry system)		0.044 mm + 0.012 mm/m (0.0017 in + 0.00014 in/ft)	
Single-point repeatability of			
portable probe		0.030 mm (0.0012 in)	
Hole position accuracy		0.050 mm (0.0020 in)	
Object Size (Recommend)		100 - 8000 mm (3.9 in - 315.0 in)	
Stand-off distance		300 mm (11.8 in)	
Depth of field		400 mm (15.7 in)	
Output formats		.stl, .obj, .ply, .asc, .igs, .txt, .mk2, .umk and etc.	
Operating temperature range		-10°C - 40°C (14°F-104°F)	
Operating humidity (Non-condensation)		10%-90% RH	
Interface mode		USB 3.0	
Certification		CE, UL	
Patents 1) ISO 17025 accredited: Based on VDI/VDE 2634 Part : 2) ISO 17025 accredited: Based on VDI/VDE 2634 Part:		CN106500627, CN106500628, CN206132003U, CN204854633U, CN204944431U, CN204902788U, CN204963812U CN204902785U, CN106403845, US10309770B2, CN204854633U, CN105068384B, CN105049664B, CN106403845B CN111694665A, CN214375417U, CN214379242U, CN214379241U, CN109000582B, CN112802002B, CN210567185U CN214121096U, CN214375417U, CN214379242U, CN214379241U, CN109000582B, CN114205483B, CN113514008A CN214121096U, CN2143794U, CN214379242U, CN214379241U, CN109000582B, CN114205483B, CN113514008A	



Its i-Tracker can also be combined with path planning software for intelligent robotic path planning and guiding.